

Product Description

- 1W LED emergency adjustable spotlight
- LiFePO4 battery technology
- 3000K as standard (4000K option available)
- Wide beam as standard (narrow beam option available)
- Surface mounting installation
- Powder coated die-cast aluminium housing


Product Image



Specification

- 3 hour rated duration
- Non-maintained operation as standard (maintained option available)
- Tridonic LiFePO4 battery technology
- Tridonic electronic components
- Surface ceiling/wall mounting
- 90° vertical adjustment, 360° horizontal adjustment LED spotlight
- IP20 ingress protection
- RAL 9003 White as standard
- Custom RAL colour available on request

Product Dimensions



Technical Data

Mode of Operation	Non-Maintained (Maintained option available)
Supply Voltage	230VAC 50/60Hz
Light Source	1W High Output 3000K (4000K option available)
Battery	TRIDONIC 3.2V 3.0Ah 2-Cell LiFePO4
Emergency Inverter	TRIDONIC EM powerLED FX LiFePO4 1 – 2 W
Re-Charge Period	24 hours from full discharge
Emergency Duration	3 hours
Test Facility	Central Test Unit (Self-Test & DALI options also available)
Ingress Protection	IP20
Finish	RAL 9003 as standard (other colours available on request)
Compliance	I.S./E.N. 60598-1, I.S./E.N. 60598-2-22, the LVD, the EMC, the ERP, the RoHS, the WEEE and the Battery European Directives