

Product Description

- 1W LED emergency exterior exit sign
- IP65 ingress protection
- LiFePO4 battery technology
- Surface mounting installation
- Polycarbonate opal pictogram
- Polycarbonate housing


Product Image



Specification

- 3 hour rated duration
- 34 metre viewing distance
- Maintained operation
- Tridonic LiFePO4 battery technology
- Tridonic electronic components
- Surface wall mounting
- IP65 ingress protection
- Grey as standard
- Custom RAL colour available on request

Product Dimensions



Technical Data

Mode of Operation	Maintained
Supply Voltage	230VAC 50/60Hz
Light Source	TRIDONIC 1W High Output 6500K LED Strip
Battery	TRIDONIC 3.2V 3.0Ah 2-Cell LiFePO4
Emergency Inverter	TRIDONIC EM powerLED FX LiFePO4 1 – 2 W
Re-Charge Period	24 hours from full discharge
Emergency Duration	3 hours
Test Facility	Central Test Unit (Self-Test & DALI options also available)
Viewing Distance	31 Metres
Ingress Protection	IP65
Finish	Grey
Compliance	I.S./E.N. 60598-1, I.S./E.N. 60598-2-22, the LVD, the EMC, the ERP, the RoHS, the WEEE and the Battery European Directives